



20' One-Side Expandable Folding Shelter



Transport Mode



Deployed Mode



SB3892.0.2S1
20' One-Side Expandable Folding Shelter

STANDARD PRODUCT FEATURES

- 20' x 8' ISO Container, 9-high stacking
- 20-minute set up time by 2 people including unloading and leveling
- Expanding section is self supporting and allows expansion and use while on a truck or trailer
- Power Input Panel (PIP) for connection to commercial power source
- CFC-free Polyurethane foam insulation thermal value: 0.56 W/m2K
- Highly mobile; can be shipped via major transport systems
- Leveling jack set, (4) each
- Optional packages available

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

Transport Mode	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	19' 10 1/2"	18' 10"	8' 0"	7' 0"	7' 8"	7' 0"	6' 8"	3' 11"
Metric	6,058	5,750	2,438	2,150	2,438	2,139	2,032	1,200

Deployed Mode	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	19' 10" 1/2"	18' 10"	7' 8"	7' 0" / 6' 8"	14' 9"	13' 11"	6' 8"	3' 11"
Metric	6,058	5,750	2,438	2,145 / 2,045	4,500	4,248	2,032	1,200

20'	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY Transport Mode	CUBIC CAPACITY Deployed Mode
Lbs	6,054	10,582	16,636	727 Cu.Ft.	1,843 Cu. Ft.
Kgs	2,764	4,800	7,546	20.6 Cu.M.	52.2 Cu. M.

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

022516-R02

ISO 9001



CERTIFIED QUALITY MANAGEMENT SYSTEM

GSA CONTRACT # GS-02F-0024P
Advantage!