
## 20' Maintenance Container





## **PRODUCT FEATURES**

## STANDARD FEATURES

- · Corrugated steel sides and roof
- 14 gauge locking steel double end swing doors on both ends and one single side door
- 1 1/8" thick marine plywood floors with 10 guage steel floor overlay
- Tie down steel lashing rings, 4000 lbs. cap. each
- · Two-way laden fork lift pockets
- · (2) closing vents
- (1) vent, pressure relief valve
- · Custom steel shelves with plywood surface
- · Tool mounting system



## NSN # 8150-01-480-6877

	LENGTH		HEIGHT		WIDTH		DOOR OPENING		SIDE DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width	Height	Width
Ft in	19' 10 1/2"	19' 2 1/16"	8' 6"	7' 9 29/32"	8' 0"	7' 5 1/16"	7' 5 3/4"	7' 8 1/8"	7' 5 3/4"	3' 10 7/16"
Metric	6,058	5,844	2,591	2,385	2,438	2,264	2,280	2,340	2,280	2,350

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY
Lbs	6,740	46,170	52,910	1,113 Cu. Ft.
Kgs	3,057	20,943	24,000	31.5 Cu. M.

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD





052621-R00

ISO 9001





ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS