



SEA BOX®

20' Collapsible Shelter

SB3893.9.MH101
 20' Collapsible Shelter



Pre-Assembled Kit (2' high)
Can be stacked 4-high

PRODUCT FEATURES

STANDARD FEATURES

- Collapsible Kit, 2' high - can be stacked 4 high
- Constructed Unit, 9' 0" high - can be stacked 3-high
- (2) sets of forklift pockets, laden and unladen
- Insulated wall panels: 9'6" H x 3.75' W x 2.75" (thick)
 - 5 (each) per long side, fully interchangeable
 - 2 (each) per short side
- 1 external door: 7' H x 3' W x 2" D furnished with handle lock, pre-painted aluminum frame
- 2 (each) double layer windows (32" x 43")
 - "Sliding" mechanism (one side fixed and one sliding)
- Electrical components
 - Distribution box, 110V single phase
 - (2) overhead lights
 - flush mounted (2) sockets and (1) switches
- Units can be connected to create a larger structure
- Thermal Conductivity Coefficient: 0.039 W/mK
- Thermal Resistance (R21 Value): 1.28 m2K/W
- Combination Heating/Cooling unit (110V)



20' Collapsible Container Interior

OPTIONAL FEATURES

- Plastic PVC rolling shutters provided
- Anti Vandal Bars for windows
- Anti Vandal Gate for door
- Resin floor covering
- Connection Kits (create larger structures)



Create larger structures with connected units

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	LENGTH		HEIGHT		WIDTH		TARE WEIGHT
	Exterior	Interior	Exterior	Interior	Exterior	Interior	
Ft in	19' 10 1/2"	19' 4 11/64"	9' 0"	8' 0"	8' 0"	7' 8 17/32"	4,299 lbs.
Metric	6,058	5,897	2,743	2,438	2,438	2,350	1,950 kg

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

000000-R00

ISO 9001:2008



CERTIFIED QUALITY
MANAGEMENT SYSTEM