



SEA BOX[®]

20ft Domino Type (1)

SB4712
 20ft Domino Type (1)



STANDARD PRODUCT FEATURES

- Full width floor
- Large internal height
- Useful optional features of tarpaulins, bale bars and ramp ends
- Five units fold into 8' 6"
- 9 high stacking at 24,000 Kgs

TYPICAL LASHINGS AND INTERFACING

- Stanchions: 4 sockets per side size 85mm
- Lashing bars: 8 x 5000kg per side, 2 per end
- Floor: 45mm softwood planks 6mm gaps
- Fork pockets: 115 x 360mm
- Twistlocks: 1 piece forged lift element, 30 degree stainless steel detent
- Header locks: 2 per end semi-automatic
- Corner locking: hammer locked conical pin
- Counterbalancing: coil tension spring
- Approvals: ABS, LRS, BV, UIC, CSC, TCT

The corrugated steel end walls fold on top of the base providing a five into 8ft 6in folded module. The platform is full width with no cut outs or recesses. The walls are spring counterbalanced for safety and ease of erection.

Although superceded by the Type (10), the Type (1) flatracks have several optional features and can be provided with:

- Tarpaulins
- Bale bars and PLS interface rails in the base
- Ramp end walls (see Type 7)

Worldwide Spare Parts

As worldwide leaders in flatrack technology, the all important spare parts are available as they have been for more than 20 years.

Patents

Please do not encourage copying of the patented structures and components.

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	EXTERNAL			
	Length	Width	Height	Folded
Ft in	19' 10 1/2"	8' 0"	8' 6"	1' 8 25/64"
Metric	6,058	2,438	2,591	518

	INTERNAL			
	Wall Panel to Panel	Mid-Post to Post	Platform Width	Height at Post
Ft in	19' 6 23/32"	18' 7 47/64"	7' 7 21/32"	7' 5 1/2"
Metric	5,962	5,683	2,328	2,270

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	LOAD OVER 2m
Lbs	6,060	68,890	74,960	44,092
Kgs	2,750	31,250	34,000	20,000

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS



ISO 9001:2008



CERTIFIED QUALITY MANAGEMENT SYSTEM