



SEA BOX®

40ft Domino Type (18) 8'6"/13'6" Telescopic Posts

SB47184
40ft Domino Type (18)
8'6"/13'6" Telescopic Posts

STANDARD PRODUCT FEATURES

- Tall cargo up to 11' 5"
- Stack tall cargo with other containers
- Used as a platform flat when folded
- End wall folding flush with the floor
- Lashing beams set into the floor
- Spare parts available worldwide
- Available for leasing
- Four units fold into 8' 6"
- 7 high stacking at 30,480 Kgs



This flatrack operates as a conventional 40ft' Type (4). But within the corner posts there is a high strength telescopic post enabling very tall cargo to be carried, stacked and toplifted by spreader. Full strength is maintained at the maximum height, achieved in five 12in steps.

This patented product includes manual hydraulic lifting of the end walls so that the different height setting can be made manually. A platform flat is created when the end frames are folded flush with the floor.

Worldwide Spare Parts

As worldwide leaders in flatrack technology, the all important spare parts are available as they have been for more than 20 years.

Patents

Please do not encourage copying of the patented structures and components.

TYPICAL LASHINGS AND INTERFACING

- Stanchions: 6 sockets per side size 85mm
- Lashing bars: 12 x 5000kg per side, 2 per end
- Cross floor lashing: 4 x 2m per floor each with: 6 x 5000kg lashing bars, 8 x 2m chocking slots
- Gooseneck tunnel: both ends
- Floor: 45mm softwood planks 6mm gaps
- Fork pockets: 115 x 360mm
- Twistlocks: 1piece forged lift element 30 degree stainless steel detent
- Header locks: 2 per end semi-automatic
- Corner locking: hammer locked conical pin
- Counterbalancing: leaf spring or coil
- Removable ends: optional use as ramps
- Approvals: ABS, LRS, BV, UIC, CSC, TCT

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	EXTERNAL				
	Length	Width	Height	Extended Height	Folded
Ft in	40' 0"	8' 0"	8' 6"	13' 6"	2' 1 1/2"
Metric	12,192	2,438	2,591	4,115	648

	EXTERNAL				
	Wall Panel to Panel	Mid-post to Post	Platform Width	Height at Post	Height when Extended
Ft in	39' 11 1/2"	37' 10 53/64"	7' 3 41/64"	6' 5"	11' 5"
Metric	12,180	11,552	2,226	1,960	3,484

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	LOAD OVER 2m
Lbs	13,000	86,200	99,200	56,000
Kgs	5,900	39,100	45,000	25,400

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS



ISO 9001:2008



CERTIFIED QUALITY
MANAGEMENT SYSTEM

031801-R40