



SEA BOX®

20ft Domino Type (5) with Open Goal Post End Frames



STANDARD PRODUCT FEATURES

- End wall folding flush with the floor
- Lashing beams set into the floor
- Removable end walls for vehicle loading
- Spare parts available worldwide
- Commonly and readily available for leasing
- Seven units fold into 8' 6"
- 9 high stacking at 24,000 Kgs

TYPICAL LASHINGS AND INTERFACING

- Stanchions: 4 sockets per side size 85mm
- Lashing bars: 8 x 5000kg per side, 2 per end
- Floor lashing beams: 4 x 2m per floor each with: 6 x 5000kg lashing bars, 8 x 2m chocking slots
- Floor: 45mm softwood planks, 6mm gaps
- Fork pockets: 115 x 360mm
- Twistlocks: 1 piece forged lift element, 30 degree stainless steel detent
- Header locks: 2 per end semi-automatic
- Corner locking: hammer locked conical pin
- Counterbalancing: leaf spring
- Removable ends: optional use as ramps
- Approvals: ABS, LRS, BV, UIC, CSC, TCT

The 20ft Type (5) folds seven into 8ft6in module. It features a 'goal post' end, which is an open frame to enable its use with certain cargo projecting through the ends.

The flat can be used as a bolster when the end frames are folded flush with the floor. A special feature of the Type (5) and (4) is the lashing beams which are unique to CSA flatracks and are essential for the Type (5) because of the need for additional longitudinal cargo securing.

The end walls can be mixed easily with the Type (4) and walls are removable for vehicle loading.

Worldwide Spare Parts

As worldwide leaders in flatrack technology, the all important spare parts are available as they have been for more than 20 years.

Patents

Please do not encourage copying of the patented structures and components.

SB4752
20ft Domino Type (5)
with Open Goal Post End Frames

030501-R20

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	EXTERNAL			
	Length	Width	Height	Folded
Ft in	19' 10 1/2"	8' 0"	8' 6"	1' 2 1/2"
Metric	6,058	2,438	2,591	370

	INTERNAL		
	Mid-Post to Post	Platform Width	Height at Post
Ft in	18' 6"	7' 3 41/64"	7' 4"
Metric	5,638	2,226	2,233

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	LOAD OVER 2m
Lbs	6,280	68,670	74,950	44,092
Kgs	2,850	31,150	34,000	20,000

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS



ISO 9001:2008



CERTIFIED QUALITY
MANAGEMENT SYSTEM