



## 20ft X 8ft 6in Diesel / Electric Refrigerated ISO Cargo Container

**SB535-6**  
20ft X 8ft 6in Diesel / Electric Refrigerated  
ISO Cargo Container



### STANDARD PRODUCT FEATURES

- Aluminum, steel or sides
- Double full opening swing doors on one end
- Forklift pockets (on some 20' units)
- Aluminum T-grade floors
- Most refrigerated machinery features electrical supply as follows: 208/230, 380/460 Volts AC, 3 phase, 50 or 60 cycle
- Temperature range from -20°F to 70°F

000000-R00

### ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD FOR NINE (9) HIGH STACKING

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
<b>Ft in</b>	19' 10 1/2"	18' 2 1/2"	8' 6"	7' 4 1/2"	8' 0"	7' 4"	7' 4 1/2"	7' 4"
<b>Metric</b>	6,058	5,550	2,591	2,248	2,438	2,235	2,248	2,235

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY
<b>Lbs</b>	6,370	60,830	67,200	985 Cu. Ft.
<b>Kgs</b>	2,889	27,591	30,480	27.9 Cu. M.

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

ISO 9001:2008



CERTIFIED QUALITY  
MANAGEMENT SYSTEM