



Tricon Dry Freight ISO Cargo Container Double Doors Both Ends (TYPE V)

SB825.0.SC.4TS
Tricon Dry Freight ISO Cargo Container
Double Doors Both Ends (TYPE V)

PRODUCT FEATURES

STANDARD FEATURES

- LOWEST TARE WEIGHT and LARGEST CUBIC CAPACITY for any Type V Tricon
- Full-width cargo doors on both ends, (swing out a full 270 degrees for ease of loading)
- (4) way fork lift pockets
- Wall tie down steel lashing rings, 4,000 lbs. cap. each (12 total)
- Door sill, recessed tie down steel lashing rings, 4,000 lbs. cap. each (4) total
- Adjustable shelving brackets (4) sets:
- (8) vertical E-track sections total
- (4) each transverse shelf, half, rated at 2,000 lbs. per half shelf
- (8) each Shoring and Deck beams
- Connecting couplers, (3) per Tricon
- Connecting coupler storage bracket (1) each
- Vents, (2) each
- Customer's choice of standard exterior paint colors



(3) Tricon Containers coupled together to form (1) 20' ISO module



OPTIONAL FEATURES

- Door corner post tie downs (20 total) = restraint system, shoring slot will support 2" x 6" lumber
- Document holder (2) each
- Rack & Cabinet systems

000000-R00

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	6' 5 1/2"	6' 4"	8' 0"	7' 4 15/16"	8' 0"	7' 8 11/64"	7' 1"	7' 8 11/64"
Metric	1,969	1,930	2,438	2,259	2,438	2,341	2,160	2,341

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY
Lbs	2,900	12,000	14,900	354 Cu. Ft.
Kgs	1,315	5,445	6,760	10.02 Cu. M.

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

ISO 9001:2008



CERTIFIED QUALITY
MANAGEMENT SYSTEM