

# Sea Box, Inc.®



## Quadcon Refrigerated ISO Cargo Container

Quadcon Reefer	Length		Height		Width		Door Opening	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Feet/Inches	4' 9 3/8"	4' 5 3/4"	8' 0"	7' 1/8"	8' 0"	7' 5 3/16"	72"	28 1/4"
Metric	1,457	1,365	2,438	2,137	2,438	2,265	1,829	718

Quadcon Reefer	Tare Weight w Machine	Payload	Gross Weight	Cubic Capacity	Thermal Leakage = U max @ 10 deg. C mean temp
Lbs.	2,600	9,300	11,900	195 Cu. Ft.	95 BTU/h deg. F
Kg.	1,179	4,219	5,398	5.52 Cu. m.	52.88 Kcal/h deg. C

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARDS FOR 9 HIGH STACKING

### — STANDARD FEATURES —

- ▶ Smooth Steel sides, roof + single swing doors
- ▶ Stainless Steel lining
- ▶ Heavy duty tread plate aluminum floor
- ▶ Four way fork lift pockets
- ▶ 208/230 Volts AC Electric Refrigeration Machinery, 3 phase; 60 cycle
- ▶ Temperature range from -20° F to 80° F
- ▶ Temp. Control display adjacent to entry door
- ▶ Fully adjustable shelving "A" tracks, fully recessed into the walls

### — OPTIONAL FEATURES —

- ▶ Connecting couplers, (3) per Quadcon
- ▶ Connecting coupler storage bracket (1) each
- ▶ Manifest box (2) each
- ▶ SS shelving (8) pieces, open wire design
- ▶ SS decking and shoring beams (16) each
- ▶ Spare parts box



Above: Temp. Control Display  
Below: Stainless Steel lining



Above: Internal lighting  
Below: Fully adjustable shelving "A" tracks



**PART # SB530.0**

Four Quadcon Containers coupled together form a 20' ISO module