

Sea Box, Inc.®



Tricon Refrigerated ISO Cargo Container

Tricon Reefer	Length		Height		Width		Door Opening	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Feet/Inches	6' 5 1/2"	6' 3/4"	8' 0"	7' 7/8"	8' 0"	7' 5 3/16"	72"	30"
Metric	1,969	1,848	2,438	2,156	2,438	2,265	1,829	762
Tricon Reefer	Tare Weight w Machine	Payload	Gross Weight	Cubic Capacity	Thermal Leakage = U max @ 10 deg. C mean temp			
lbs.	3,360	14,277	17,637	282 cu. ft.	9.00 W/K			
kg.	1,524	6,476	8,129	8.0 cu. m.	7.74 Kcal/deg. K			

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARDS FOR 9 HIGH STACKING

— STANDARD FEATURES —

- ▶ Smooth Steel sides, roof + single swing door
- ▶ Stainless Steel lining
- ▶ Heavy duty tread plate aluminum floor
- ▶ Four way fork lift pockets
- ▶ Thermo King VM405 Refrigeration Unit
- ▶ Temp. Control display adjacent to entry door
- ▶ 25ft power cable
- ▶ Fully adjustable shelving "A" tracks, fully recessed into the walls
- ▶ Internal lighting, dual voltage 110/220 VAC

— OPTIONAL FEATURES —

- ▶ Connecting couplers, (3) per Tricon
- ▶ Connecting coupler storage bracket (1) each
- ▶ Manifest box (2) each
- ▶ SS shelving (8) pieces, open wire design
- ▶ SS decking and shoring beams (16) each
- ▶ Spare parts kit



Above: Temp. Control Display
Below: Stainless Steel lining



Above: Internal lighting
Below: Fully adjustable shelving "A" tracks



PART # SB531.0

Three Tricon Containers coupled together form a 20' ISO module!