

20ft Domino Type (10) corrugated walls fold on floor



This flatrack benefits from a full width cargo deck, platform flat use when folded and high cube. In the commercial market it is a popular model. The corrugated steel end walls lie directly on top of the floor to become load bearing. Thus it can be used as a platform flat for long cargos such as pipes or sawn timber. Internal height is better than a Type (4) and seven units fold into 8ft6in. This is one of 20 patent designs exclusive to CSA licensees.

The end walls are removable and can be laid for use as a loading ramp for tyred vehicles up to 1.5 tonne axle load. The tare weight is low and the payload can be increased to high level making this a highly versatile workhorse.

Worldwide Spare Parts

As worldwide leaders in flatrack technology, the all important spare parts are available as they have been for more than 20 years.

Patents

Please do not encourage copying of the patented structures and components.



Part # SB47102

Typical Lashings and Interfacing

Stanchions:	4 sockets per side size 85mm
Lashing bars:	8 x 5000kg per side, 2 per end
Floor:	45mm softwood planks 6mm gaps
Fork pockets:	115 x 360mm
Twistlocks:	1 piece forged lift element, 30° stainless steel detent
Header locks:	2 per end semi-automatic
Corner locking:	hammer locked conical pin
Counterbalancing:	leaf spring
Removable ends:	optional use as ramps
Approvals:	ABS, LRS, BV, UIC, CSC, TCT

Typical Dimensions

External	mm	ft	in
Length	6058	19'	10.5"
Width	2438	8'	0"
Height	2591	8'	6"
Folded	370	1'	2.5"

7 into 8ft6in

Internal	mm	ft	in
Wall panel to panel	5962	19'	6.7"
Post to post	5578	18'	3.6"
Platform width	2358	7'	8.8"
Height at post	2270	7'	5.5"

Typical ratings	kg	lb
Tare weight	2750	6060
Payload	31250	68890
Gross	34000	74960
Load over 2m	20000	44092
Stacking	9 high at 24000kg	

The Flatrack Features

- Use an occasional platform flat when folded
- Full width cargo deck
- Floor clear of recess over full length
- Removable end walls for vehicle loading
- End walls can be laid at loading ramps
- Spare parts available worldwide
- Commonly available

Please Contact

Clive-Smith Associates Ltd's agent: -

Sea Box Inc.	Tel	1 856 303 1101
876 Land Street	Fax	1 856 303 1501
East Riverton	Email	jimb@seabox.com
NJ 08077	Web	www.seabox.com
USA		

Patents granted & pending