

## 40ft Domino Type (6) lightweight hi-cube



Similar to the Type (4) where the end walls fold flush with the floor but with a shallow base and folding 6 units into 8ft6in. This is one of 20 patent designs exclusive to CSA licensees.

The Type (6) has a flat panelled end wall which folds flush with the base. When folded it can be used as a 40ft platform flat. The base includes four full width cross floor lashing recesses which will support chocking blocks, lashing chains, straps etc. The end wall can be removable for vehicle loading. The floor surface is virtually continuous through recess zones.

### Worldwide Spare Parts

As worldwide leaders in flatrack technology, the all important spare parts are available as they have been for more than 20 years.

### Patents

Please do not encourage copying of the patented structures and components.



**Part # SB4764**

### Typical Lashings and Interfacing

Stanchions:	6 sockets per side size 85mm
Lashing bars:	12 x 5000kg per side, 2 per end
Floor lashing beams:	4 x 2m per floor each with: 6 x 5000kg lashing bars, 8 x 2m chocking slots
Gooseneck tunnel:	both ends
Floor:	45mm softwood planks 6mm gaps
Fork pockets:	115 x 360mm
Twistlocks:	1 piece forged lift element, 30° stainless steel detent
Header locks:	2 per end semi-automatic
Corner locking:	hammer locked conical pin
Counterbalancing:	leaf spring or coil
Removable ends:	optional use as ramps
Approvals:	ABS, LRS, BV, UIC, CSC, TCT
Options:	sling lift points, post extensions

### Typical Dimensions

External	mm	ft	in
Length	12192	40'	0"
Width	2438	8'	0"
Height	2895	9'	6"
Folded	432	1'	5"

6 into 8ft6in

Internal	mm	ft	in
Wall panel to panel	12180	39'	11.5"
Mid-post to post	11652	38'	2.7"
Platform width	2226	7'	3.6"
Height at post	2473	8'	1.3"

Typical ratings	kg	lb
Tare weight	5100	11240
Payload	30900	68120
Gross	36000	79360
Load over 2m	20000	44090
Stacking		7 high at 30480

### The Flatrack Features

- **Hi-cube and 6 in 8ft6in folding**
- **End wall folding flush with the floor**
- **Lashing beams set into the floor**
- **Removable end walls for vehicle loading**
- **Spare parts available worldwide**
- **Commonly and readily available for leasing**

### Please Contact

Clive-Smith Associates Ltd's agent:-

Sea Box Inc.	Tel	1 856 303 1101
876 Land Street	Fax	1 856 303 1501
East Riverton	Email	jimb@seabox.com
NJ 08077	Web	www.seabox.com
USA		