



STANDARD FEATURES:

- Corrugated steel sides, roof, & swing doors on one side
- Heavy duty steel floor
- (4) way fork lift pockets
- Wall tie down steel lashing rings, 4,000 lbs. cap. each, (28) total
- Front corner post tie downs, (10) total
- Door corner post tie downs, (10) total = restraint system, shoring slot will support 2" x 6" lumber
 Adjustable shelving brackets:
- (5) sets = (10) Vertical E-Track sections total - Vents, (2) each

OPTIONAL FEATURES:

- Manifest Box, (2) each
- Connecting couplers, (3) per Tricon
- Connecting coupler storage bracket, (1) each
- Decking and Shoring Beams, (15) each
- 383 Green exterior CARC paint

(3) Tricon Containers coupled together to form one 20' ISO module

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARDS

TRICON	Length		Height		Width		Door Opening	
	Ext.	Int.	Ext.	Int.	Ext.	Int.	Height	Width
Ft. / In.	6' 5 1/2"	6' 3 5/16"	8' 0"	7' 5 1/64"	8' 0"	7' 7 23/32"	7' 1 3/64"	6' 1 45/64"
Metric	1,969	1,913	2,438	2,261	2,438	2,330	2,160	1,872

TRICON	Tare Weight	Payload	Gross Weight	Cubic Capacity
Lbs.	2,580	12,320	14,900	356 Cu. Ft.
Kg.	1,170	5,590	6,760	10.0 Cu. M.

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

SB821-0

ouble Doors One Side (TYPE 1) ricon Dry Freight ISO Cargo Cont<u>aine</u>r



092410-R00





CORPORATE OFFICE 1 Sea Box Drive Cinnaminson, NJ 08077 Tel: (856) 303-1101 Fax: (856) 303-1501 Email: sales@seabox.com www.seabox.com

