

Sea Box, Inc.®

CORPORATE OFFICE
 802 Industrial Hwy.
 East Riverton, NJ 08077-1910
 Tel: (856) 303-1101
 Fax: (856) 303-1501
www.seabox.com
 e-mail: sales@seabox.com



NSF Certified Production January 26, 2009

SMALL FIELD REFRIGERATED SYSTEM (SFRS)

Tricon Reefer	Length		Height		Width		Door Opening	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Feet/Inches	6' 5 1/2"	5' 11 11/16"	8' 0"	6' 0"	8' 0"	7' 3 5/16"	75"	28"
Metric	1,969	1,820	2,438	2,134	2,438	2,218	1,905	711

Tricon Reefer	Tare Weight w Machine	Payload	Gross Weight	Cubic Capacity Dry Freight	Cubic Capacity Reefer Cargo	Thermal Leakage = U max @ 10 deg. C mean temp
lbs.	3,520	11,480	15,000	300 Cu. Ft	281.6 Cu. Ft	7.49 W/K
kg.	1,597	5,207	6,804	8.5 Cu. M	8.0 Cu. M	6.46 Kcal/Hr °C

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARDS FOR 9 HIGH STACKING

— STANDARD FEATURES —

- ▶ Smooth Steel sides, roof + single swing door
- ▶ Stainless Steel lining per NSF standards
- ▶ Heavy duty tread plate aluminum floor
- ▶ Four way fork lift pockets, USMC compatible
- ▶ Thermo King VM405 PBBD2 Refrigeration Unit 208/230 VAC, 3phase 50/60 Hz
- ▶ 20ft power cable with IEC 60309 plug
- ▶ Vertical E-Track, (12) sticks total
- ▶ Internal lighting, dual voltage source 115/230 VAC
- ▶ Connecting couplers, (3) per Tricon
- ▶ Connecting coupler storage bracket (1) each
- ▶ Steps/Hand 5 each holds for access to non slip roof
- ▶ Manifest box (1) each
- ▶ Air Curtains in sliding track across door
- ▶ 31-day recording thermostat

— OPTIONAL FEATURES —

- ▶ Fiberglass shelving, open deck design, available in either 21 1/4" or 30" widths
- ▶ Decking and shoring beams extendable type
- ▶ Web straps and ratchets
- ▶ Clip-On Diesel Generator Set, can run 3 Tricons at once
- ▶ Spare parts kit



Fiberglass shelving
 21 1/4" or 30" widths (option)



Internal lighting
 dual voltage source 115/230 VAC



Clip-On Diesel Generator Set
 (Option)



Air Curtains
 Stainless Steel Lining

PART # SB531.0.SFRS