

Sea Box, Inc.®

CORPORATE OFFICE
 802 Industrial Hwy.
 East Riverton, NJ 08077-1910
 Tel: (856) 303-1101
 Fax: (856) 303-1501
www.seabox.com
 e-mail: sales@seabox.com



20' X 8' 0" Refrigerated ISO Cargo Container

20' Refrigerated	Length		Height		Width		Door Opening	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Feet/Inches	19' 10 1/2"	18' 3/8"	8' 0"	6' 11 5/16"	8' 0"	7' 6 5/16"	6' 9 25/32"	7' 6 5/16"
Metric	6,058	5,496	2,438	2,116	2,438	2,294	2,077	2,294

20' Refrigerated	Tare Weight	Payload	Gross Weight	Cubic Capacity
Lbs.	7,720	45,080	52,800	944 Cu. Ft.
Kg.	3,502	20,498	24,000	26.7 Cu. M.

* All dimensions are average. Exact specifications for each model are available.

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARDS FOR 9 HIGH STACKING

— STANDARD FEATURES —

- ▶ Double swing doors with tethered padlock
- ▶ Sliding Air curtain
- ▶ Emergency escape hatch
- ▶ Aluminum T-grade floors
- ▶ Stainless steel interior lining
- ▶ 4 rows of "E" Track cargo restraint system along interior side walls of container (these may all be used for numerous tie downs)
- ▶ 6 floor cargo tie downs (close to each wall)
- ▶ 6 wall cargo tie downs high up on both walls (24 total tie downs)
- ▶ Interior lighting system, works on 110 or 460 VAC
- ▶ Forklift pockets (2 sets; 1 laden, 1 set special unladen)
- ▶ Access steps to non-slip roof
- ▶ Pressure relief port installed in rear cargo door panel, for air transport
- ▶ Carrier refrigerated machinery features electrical supply as follows: Dual Voltage 208/230 or 460 Volts AC, 3 phase, 50/60hz
- ▶ Temperature range from -22° F to +86° F
- ▶ CARC Tan Exterior Paint



Double swing doors with escape hatch



Air Curtain



Stainless steel interior lining

PART # SB541.0