

# Sea Box, Inc.®

**CORPORATE OFFICE**  
 802 Industrial Hwy.  
 East Riverton, NJ 08077-1910  
 Tel: (856) 303-1101  
 Fax: (856) 303-1501  
[www.seabox.com](http://www.seabox.com)  
 e-mail: [sales@seabox.com](mailto:sales@seabox.com)



**GSA Advantage!**  
[www.gsaAdvantage.gov](http://www.gsaAdvantage.gov)  
 CONTRACT # GS-02F-0024P

## Tricon (TYPE V) ISO Cargo Container Double Doors Both Ends Patent Pending

Tricon	Length		Height		Width		Door Opening	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Feet/Inches	6' 5 1/2"	6' 4"	8' 0"	7' 4 15/16"	8' 0"	7' 9 9/16"	7' 1"	7' 8 11/64"
Metric	1,969	1,930	2,438	2,259	2,438	2,306	2,160	2,341

Tricon	Tare Weight	Payload	Gross Weight	Cubic Capacity
Lbs.	2,900	12,000	14,900	354 Cu. Ft.
Kg.	1,315	5,445	6,760	10.02 Cu. M.


### — STANDARD FEATURES —

- ▶ **LOWEST TARE WEIGHT and LARGEST CUBIC CAPACITY** for any Type V Tricon
- ▶ Full-width cargo doors on both ends, (swing out a full 270° for ease of loading)
- ▶ (4) way fork lift pockets
- ▶ (10) each floor level steel tie down lashing rings
- ▶ (10) each top side rail, steel, tie down lashing rings, all lashing rings are 4,000 lbs. cap. each
- ▶ Adjustable shelving brackets (3) sets:
  - (6) vertical E-track sections total
  - (2) Full size shelving system provides
  - (4) each longitudinal shelf half, Non-Absorbing Composite Shelves
  - Each full size shelving system is rated at 2,000 lbs. cap.
  - (6) each Shoring and Deck beams
- ▶ Connecting couplers, (3) per Tricon
- ▶ Connecting coupler storage bracket (1) each
- ▶ Vents, (2) each
- ▶ Customer's Choice of Standard Exterior Paint Color

### — OPTIONAL FEATURES —

- ▶ Adjustable Shelving Brackets (4) sets total
- ▶ Adjustable Shelving Brackets (5) sets total
- ▶ Door still, recessed tie down steel lashing rings, 4,000 lbs. cap. each (4) total
- ▶ Document holder (2) each

**ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARDS FOR 9 HIGH STACKING**



(3) Tricon Containers can be coupled together to form (1) 20' ISO module!

**PART # SB825.0.SC.4LSH**