





802 Industrial Hwy. East Riverton, NJ 08077-1910

Tel: (856) 303-1101 Fax: (856) 303-1501 www.seabox.com e-mail: sales@seabox.com





Tricon (TYPE 5) ISO Cargo Container Double Doors Both Ends Patent Pending

Tricon	Length		Height		Width		Door Opening		
	Exterio	r Interior	Exteri	or Interior	Exterior	r Interior	F	Ieight	Width
Feet/Inches	6' 5 1/2'	" 6' 4"	8' 0''	7' 4 15/16''	8' 0''	7' 6 9/16''		7' 1''	7' 8 11/64''
Metric	1,969	1,930	2,438	2,259	2,438	2,306	2	,1630	2,341
Tricon	Tare Weight			Payload		Gross Weight		Cubic Capacity	

Tricon	Tare Weight	Payload	Gross Weight	Cubic Capacity
Lbs.	2,986	11,914	14,900	354 Cu. Ft.
Kg.	1,354	5,404	6,758	10.02 Cu. M.

— STANDARD FEATURES —

- LOWEST TARE WEIGHT and LARGEST CUBIC **CAPACITY for any Type 5 Tricon**
- Full-width access cargo doors on both ends of the container, (swing out a full 270° for ease of loading)
- (4) way fork lift pockets
- (10) each floor level steel tie down lashing rings (10) each top side rail, steel, tie down lashing rings, all lashing rings are 4,000 lbs. cap. each (20) Total
- (3) each Door sill plus 2 centered on sidewall, recessed floor tie down steel lashing rings, 4,000 lbs. cap. each (8) total
- (6) vertical logistic tracks ("A" or "E" series)
 - (2) Full size shelving system provides
 - (4) each longitudinal shelf half,

Non-Absorbing Composite Shelves

Each full size shelving system is rated at 2,000 lbs. cap.

- (6) each Shoring and Deck beams
- Connecting couplers, (3) per Tricon
- Connecting coupler storage bracket (1) each
- Vents, (2) each
- Lusterless Aircraft Insignia White Color (37875)

— OPTIONAL FEATURES —

- Full size shelving systems + 3 shoring and decking beams kit
- Ratchet and Web Strap Assembly (SB3400)
- Articulated Track Fitting with D-Ring (SB3410)
- Document holder (2) each
- Rack & Cabinet systems






ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARDS FOR 9 HIGH STACKING

DRY FREIGHT CONTAINER. ALL CORTEN STEEL MONOCOQUE WELDED CONSTRUCTION

CONFORMING TO ISO 668 + 1496 CSC CERTIFIED



(3) Tricon Containers can be coupled together to form (1) 20' ISO module!



