

## 40ft Domino Type (5) with open goal post end frames



A heavy duty flatrack where the end walls fold flush with the floor. Four units fold into 8ft6in. This is one of 20 patent designs exclusive to CSA licensees. It features a 'goal' post end comprising an open frame to enable its use with certain cargo projecting through the ends.

The flat can be used as a bolster when the end frames are folded flush with the floor. A special feature of the Type (5) (and (4)) is the lashing beams which are unique to CSA flatracks and are essential for the Type (5) because of the need for additional longitudinal cargo securing.

### Worldwide Spare Parts

As worldwide leaders in flatrack technology, the all important spare parts are available as they have been for more than 20 years.

### Patents

Please do not encourage copying of the patented structures and components.



Part # SB4754

### Typical Lashings and Interfacing

Stanchions:	6 sockets per side size 85mm
Lashing bars:	12 x 5000kg per side, 2 per end
Floor lashing beams:	4 x 2m per floor each with: 6 x 5000kg lashing bars, 8 x 2m chocking slots
Gooseneck tunnel:	both ends
Floor:	45mm softwood planks 6mm gaps
Fork pockets:	115 x 360mm
Twistlocks:	1 piece forged lift element, 30° stainless steel detent
Header locks:	2 per end semi-automatic
Corner locking:	hammer locked conical pin
Counterbalancing:	leaf spring or coil
Removable ends:	optional use as ramps
Approvals:	ABS, LRS, BV, UIC, CSC, TCT
Options:	Sling lift points, post extensions

### Typical Dimensions

External	mm	ft	in
Length	12192	40'	0"
Width	2438	8'	0"
Height	2591	8'	6"
Folded	648	2'	1.5"
		4 into 8ft6in	

Internal	mm	ft	in
Mid-post to post	11652	38'	2.7"
Platform width	2226	7'	3.6"
Height at post	1955	6'	5"

Typical ratings	kg	lb
Tare weight	4900	10800
Payload	45100	99430
Gross	50000	110230
Load over 2m	25400	56000
Stacking		7 high at 30480

### The Flatrack Features

- End frame folding flush with the floor
- 50 ton gross or more
- Lashing beams set into the floor
- Removable end frame for vehicle loading
- Spare parts available worldwide
- Commonly and readily available for leasing

### Please Contact

Clive-Smith Associates Ltd's agent:-

Sea Box Inc.	Tel	1 856 303 1101
876 Land Street	Fax	1 856 303 1501
East Riverton	Email	jimb@seabox.com
NJ 08077	Web	www.seabox.com
USA		

Patents granted & pending