

20ft Domino Type (8) Pallet-wide flatrack



The special feature of this flatrack is seen in the bottom corners. The floor space is not obstructed by the bulk of the corner post hinge; thus allowing square boxes and cargo to be stacked right up into these corners. The end walls are of corrugated steel and the end walls counterbalanced for manual operation.

The internal height is good and the unit folds six into 8ft6in for economical storage and shipping. It can be supplied with side gates, which can be returned shipped on the floor within the folded end wall space. Production units feature an 80,000lb payload though lower tare weight and payload are available as an option.

Worldwide Spare Parts

As worldwide leaders in flatrack technology, the all important spare parts are available as they have been for more than 20 years.

Patents

Please do not encourage copying of the patented structures and components.



Part # SB4782

Typical Lashings and Interfacing

Stanchions:	4 sockets per side size 85mm
Lashing bars:	8 x 5000kg per side, 2 per end
Cross floor lashing:	4 x 2m per floor each with: 6 x 5000kg lashing bars, 8 x 2m chocking slots
Floor:	45mm softwood planks 6mm gaps
Fork pockets:	115 x 360mm
Twistlocks:	1 piece forged lift element, 30° stainless steel detent
Header locks:	2 per end semi-automatic
Corner locking:	hammer locked conical pin
Counterbalancing:	leaf spring
Removable ends:	optional use as ramps
Approvals:	ABS, LRS, BV, UIC, CSC, TCT

Typical Dimensions

External	mm	ft	in
Length	6058	19'	10.5"
Width	2438	8'	0"
Height	2591	8'	6"
Folded	518	1'	8.4"
		5 into 8ft6in	

Internal	mm	ft	in
Wall panel to panel	5962	19'	6.7"
Mid-post to post	5683	18'	7.7"
Platform width	2328	7'	7.7"
Height at post	2270	7'	5.4"

Typical ratings	kg	lb
Tare weight	2750	6060
Payload	31250	68890
Gross	34000	74960
Load over 2m	20000	44092
Stacking		9 high at 24000kg

The Flatrack Features

- **Very good cargo space into the corners**
- **Ideal for square cargo**
- **Accepts European and Australian pallets**
- **End walls can be removed for vehicle and cargo loading through the ends**
- **Tarpaulin option**

Please Contact

Clive-Smith Associates Ltd's agent:-

Sea Box Inc.	Tel	1 856 303 1101
876 Land Street	Fax	1 856 303 1501
East Riverton	Email	jimb@seabox.com
NJ 08077	Web	www.seabox.com
USA		