



## 40' x 9' 6" Dry Freight ISO Cargo Container



### PRODUCT FEATURES

#### STANDARD FEATURES

- Corrugated steel sides and roof
- 14 gauge locking steel double end swing doors
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs. per 44 square inches
- Wall tie down steel lashing rings, 6,000 lbs. cap. each
- Front corner post tie downs
- Door corner post tie downs = restraint system, shoring slot will support 2" x 6" lumber
- Vents, (2) each



#### OPTIONAL FEATURES

- Manifest Box, (2) each
- Adjustable shelving brackets, (12) sets
- Decking and shoring beams, (36) each

#### ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
<b>Ft in</b>	40' 0"	39' 5 3/4"	9' 6"	8' 10 1/4"	8' 0"	7' 8 1/2"	8' 5 3/4"	7' 8 1/16"
<b>Metric</b>	12,192	12,033	2,896	2,289	2,438	2,350	2,585	2,338

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY
<b>Lbs</b>	8,530	58,670	67,200	2,690 cu. ft.
<b>Kgs</b>	3,870	26,610	30,480	76.2 cu. m.

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

**SB461.9 RENTAL**  
40' x 9' 6" Dry Freight ISO Cargo Container

051415-R00

ISO 9001:2008



CERTIFIED QUALITY MANAGEMENT SYSTEM

GSA CONTRACT # GS-02F-0024P  
**Advantage!**