



40' X 9' 6" High Cube Dry Freight Container, (4) Double Doors One End and One Side



STANDARD FEATURES

- 4 sets of 14 gauge locking steel double swing doors curb side
- 1 set of 14 gauge locking steel double swing doors on rear end
- Internal roadside wall with (20) lashing rings, Internal Curbside door wall with (12) lashing rings
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs per 44 square inches
- Vents, (4) each

- Door corner post tie downs = restraint system, shoring slot will support 2" x 6" lumber
- Front corner post tie downs
- 14 gauge locking steel double swing doors

OPTIONAL FEATURES

- Manifest box (2) each
- Adjustable shelving brackets
- Web strap and ratchet assemblies
- Call for additional Optional Features

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

| | LENGTH | | HEIGHT | | WIDTH | | DOOR OPENING | |
|---------------|----------|--------------|----------|-----------|----------|------------|--------------|-----------|
| | Exterior | Interior | Exterior | Interior | Exterior | Interior | Height | Width |
| Ft in | 40' 0" | 39' 5-11/16" | 9' 6" | 8' 8-3/8" | 8' 0" | 7' 6-3/16" | 8' 3-15/16" | 7' 8-1/8" |
| Metric | 12,192 | 12,032 | 2,896 | 2,651 | 2,438 | 2,290 | 2,538 | 2,340 |

| | TARE WEIGHT | PAYLOAD | GROSS WEIGHT | CUBIC CAPACITY |
|------------|-------------|---------|--------------|----------------|
| Lbs | 9,830 | 57,370 | 67,200 | 2,578 cu. ft. |
| Kgs | 4,460 | 26,020 | 30,480 | 73 cu. m. |

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS