

40' x 8' 6" Insulated Storage Container With Climate Control



STANDARD PRODUCT FEATURES

- · Full opening swing cargo doors on (1) end
- · Aluminum T-grade floors
- · 3" thick foam insulation including the floor
- · Heavy gauge plastic or stainless steel interior lining
- · BARD wall mounted heat pump with dehumidification
- · 2-ton cooling with 4 kw heat
- · 230/208 volts, single phase, 60 amps
- Temperature range +65F to +75F
- · Dehumidify to 45%
- · 50' power cable

Metric

- · Thermostat/de-humidistat
- · Three interior lights with switch
- · Watertight exterior circuit breaker panel

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	40' 0'	38' 0"	8' 6"	7' 3 5/8"	8' 0"	7' 5 5/8"	7' 6 1/2"	7' 5 5/8"
Metric	12,192	11,582	2,591	2,226	2,438	2,276	2,299	2,276
Unit Tare	Weight		Payload		Gross Weight		Cubic Capacity	
Lb	8,300		59,990		67,200		2,139 cu ft	

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

27,210

040522-R00

3,765

60.6 cu m

30,480