


Doors One End





STANDARD FEATURES

- · Corrugated steel sides, roof + swing doors on (1) end
- · Door shall have "Customs TIR plate" + security hub
- · 1 set of laden forklift pockets
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs per 44 square inches
- · 8 bottom rail Relief Notches
- · Wall tie down steel lashing rings, 4,000 lbs. cap. each (40 total) tested at 6,000 lbs.
- 5 front corner post tie downs (10 total)
- 5 door corner post tie downs (10 total) = restraint system, shoring slot will support 2" x 6" lumber
- · Exterior Paint Military Standard Light Green #34102 or Desert Tan #33446

- Interior Paint Military standard gray #36622
- · IMDG code, Class I, explosives, Div. 1.1 for ordinary stowage
- · Stamped corner fittings, serial #'s
- · Vents, (2) each
- · Manifest box (2) each
- All Markings are stencil paint color black #37038

OPTIONAL FEATURES

- · Exterior paint green or tan CARC paint
- · Interior paint may match exterior top coat paint
- Full payload (1.0p) certified both end walls

041122-R00

TRADE AGREEMENTS COMPLIANT

NSN-8150-01-463-8555

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	40' 0"	39' 5-3/4"	8' 6"	7' 10-1/16"	8' 0"	7' 8-1/2"	7' 5-12/16"	7' 8-1/16"
Metric	12,192	12,033	2,591	2,289	2,438	2,350	2,280	2,338

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY
Lbs	8,060	47,928	55,988	2,386 Cu. Ft.
Kgs	3,655	21,740	25,395	67.6 Cu.M.

CERTIFIED QUALITY MANAGEMENT SYSTEM

ISO 9001

CONTRACT # GS-02F-0024P GSA Advantage!™

Email: sales@seabox.com

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS