



20ft Domino Type (3) with Free Standing Corner Posts

SB4732
20ft Domino Type (3)
with Free Standing Corner Posts



STANDARD PRODUCT FEATURES

- Ideal for over width, over length cargo
- Can be fitted with telescopic posts
- Mix and match with Type (4) end wall
- Typical cargo of pipes, bars, vehicles, boats and odd shaped cargo with projecting parts
- Five units fold into 8' 6"
- 9 high stacking at 24,000 Kgs

The free standing corner post unit is unique to CSA in having full ISO transverse and longitudinal racking strength and rigidity. This unit is not to be confused with others having lightweight posts and reduced strength. These units are in service throughout the world with companies such as Evergreen, Samskip and Genstar.

TYPICAL LASHINGS AND INTERFACING

- Stanchions: 4 sockets per side size 85mm
- Lashing bars: 8 x 5000kg per side, 2 per end
- Floor: 45mm softwood planks 6mm gaps
- Fork pockets: 115 x 360mm
- Twistlocks: 1 piece forged lift element 30 degree stainless steel detent
- Header locks: 2 per end semi-automatic
- Corner locking: Conpac MK2 sliding post
- Approvals: ABS, LRS, BV, UIC, CSC, TCT

Worldwide Spare Parts

As worldwide leaders in flatrack technology, the all important spare parts are available as they have been for more than 20 years.

Patents

Please do not encourage copying of the patented structures and components.

030301-R20

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	EXTERNAL			
	Length	Width	Height	Folded
Ft in	19' 10 1/2"	8' 0"	8' 6"	1' 8 25/64"
Metric	6,058	2,438	2,591	518

	INTERNAL		
	Mid-Post to Post	Platform Width	Height at Post
Ft in	6' 7 1/2"	6' 7"	6' 9 39/64"
Metric	2,018	2,006	2,073

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	LOAD OVER 2m
Lbs	7,060	67,900	74,960	44,092
Kgs	3,200	30,800	34,000	20,000

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS



ISO 9001



CERTIFIED QUALITY
MANAGEMENT SYSTEM