



20' FLATRACK With Ramp on Both End Walls ISO Cargo Container



PRODUCT FEATURES

STANDARD FEATURES

- Both end walls fold outward to serve as a ramp with the additional wheel ramps for ease of loading trucks
- Ramp end walls are counter balanced for 2-man operation
- Storage pockets are provided for wheel ramps
- Both end walls folding flush with the floor
- 30-ton gross or more
- Spare parts available worldwide
- Designed for vehicles with 10,000 lbs. cap. (per axle) on both ramps

TYPICAL LASHINGS AND INTERFACING

- Floor: 45mm softwood planks, 6mm gaps
- Fork pockets: 115 x 360mm
- Twistlocks: 1 piece forged lift element, 30 degree stainless steel detent
- Header locks: 2 per end semi-automatic
- Corner locking: hammer locked conical pin
- Approvals: ABS, LRS, BV, UIC, CSC, TCT

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

20' FLATRACK	LENGTH		HEIGHT		WIDTH		HEIGHT COLLAPSED
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height
Ft in	19' 10 1/2"	19' 6"	8' 6"	7' 5 1/2"	8' 0"	7' 11"	1' 2 1/2"
20' FLATRACK	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		9-HIGH STACKING
Lbs	6,700		68,260		74,960		48,000 Gross Weight

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

SB4773
20' FLATRACK With Ramp on Both End Walls
ISO Cargo Container

000000-R00

ISO 9001



CERTIFIED QUALITY
MANAGEMENT SYSTEM

CONTRACT # GS-02F-0024P
GSA Advantage!