



SB485
20' Tow 2 Go
Triaxle Trailer

20' Tow 2 Go Triaxle Trailer



STANDARD PRODUCT FEATURES

- Designed to carry one standard 20' ISO Container, 20' Box Office, or a 20' Cold Storage 2 Go reefer
- (3) Axles, rated at 5,200 lbs. each
- 225/75R15 2600 lbs. D Rated Tires
- Jack rated at 12,500 lbs.
- Towing vehicle capacity: 15,600 lbs.
- (4) Heavy duty twistlocks
- 23" rear step
- Pintle Hook connection
- Loading capacity not to exceed GVWR



• 011823-R00

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

WEIGHT & DIMENSIONS							
	Length Chassis	Length Deck	Height	Width	Tare Weight	GVWR	GAWR
Ft in	24' 9'	19' 10 1/2"	2' 10"	8' 0"	2,420lbs.	15,600lbs.	5,200 lbs.
Metric	7,544	6,058	863	2,438	1,098 kg.	7,076 kg.	2359 kg.

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS