



# SEA BOX®

## Tricon Refrigerated Cargo Container

**SB531.0**  
 Tricon Refrigerated Cargo Container



Three Tricon Containers coupled together form a 20' ISO module!



Temp. Control Display



Stainless Steel lining



Internal lighting



Fully adjustable shelving "A" tracks

### PRODUCT FEATURES

#### STANDARD FEATURES

- Smooth Steel sides, roof + single swing door
- Stainless Steel lining
- Heavy duty tread plate aluminum floor
- Four way fork lift pockets
- Refrigeration Unit, 208/230 VAC, 3-phase, 30/60 Hz power
- 25ft power cable
- Fully adjustable shelving "A" tracks, fully recessed into the walls

#### OPTIONAL FEATURES

- Connecting couplers, (3) per Tricon
- Connecting coupler storage bracket (1) each
- Manifest box (2) each
- SS shelving (8) pieces, open wire design
- SS decking and shoring beams (16) each
- Spare parts kit

**NSN #: 4130-01-565-7655**

*This Equipment is Intended for the Storage of Food in the Original Sealed Package Only.*

#### ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
<b>Ft in</b>	6' 5 1/2"	6' 3/4"	8' 0"	7' 7/8"	8' 0"	7' 5 3/16"	6'	2' 6"
<b>Metric</b>	1,969	1,848	2,438	2,156	2,438	2,265	1,829	762

	TARE WEIGHT w/ MACHINE	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY	THERMAL LEAKAGE = U MAX @ 10°C MEAN TEMP
<b>Lbs</b>	3,360	14,277	17,637	282 Cu. Ft.	9.00 W/K
<b>Kgs</b>	1,524	6,476	8,129	8.0 Cu. M.	7.74 Kcal/deg. K

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

012924-R00

ISO 9001



CERTIFIED QUALITY  
MANAGEMENT SYSTEM