



20' X 8' 6" Diesel / Electric Refrigerated ISO Cargo Container



SB535-6
20' X 8' 6" Diesel / Electric Refrigerated
ISO Cargo Container

STANDARD PRODUCT FEATURES

- Aluminum, steel or sides
- Double full opening swing doors on one end
- Forklift pockets (on some 20' units)
- Aluminum T-grade floors
- Most refrigerated machinery features electrical supply as follows:
208/230, 380/460 Volts AC, 3 phase, 50 or 60 cycle
- Temperature range from -20°F to 70°F



022516-R01

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD FOR NINE (9) HIGH STACKING

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	19' 10 1/2"	18' 2 1/2"	8' 6"	7' 4 1/2"	8' 0"	7' 4"	7' 4 1/2"	7' 4"
Metric	6,058	5,550	2,591	2,248	2,438	2,235	2,248	2,235

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY
Lbs	6,370	60,830	67,200	985 Cu. Ft.
Kgs	2,889	27,591	30,480	27.9 Cu. M.

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

ISO 9001



CERTIFIED QUALITY
MANAGEMENT SYSTEM