



SEA BOX®

20' X 8' 6" Refrigerated ISO Cargo Container



20' Stainless Steel Refrigerated Container



Road Side Cargo Door Front Compartment with 2 Shelf Sets



Rear Compartment with 3 Shelves

STANDARD PRODUCT FEATURES

- (1) set of laden fork lift pockets
- (1) double full opening swing cargo doors on one end with sealable screened ventilation port
- (1) single cargo door on one side
- Emergency escape door hardware on both rear and side doors
- Heavy-duty aluminum floor, reinforced for pallet use
- Refrigeration unit: Carrier model # 69-NT40 380/460 VAC, 3 phase, 50-60 Hz and 380/460 plug
- Temperature range from -25C to 25C
- (1) moveable interior wall partition (creates 2 compartments)
- (2) internal lights with (2) switches (1 per compartment)
- (2) "locked in" alarm buttons (1 per compartment)
- (5) sets shelves, food grade with 5 web straps
- Brackets for clip-on generator are provided
- Warranty, 3 year on Carrier unit
- Certified: ATP, NZ, AU, EEC, USDA Health Code & Food Hygiene
- ISO certified, customs approved, UIC, TIR
- Operations manual and parts list manual



Moveable Partition makes 2 Compartments

OPTIONAL PRODUCT FEATURES

- Step down transformer for 220/230V, 3 phase, 50-60 Hz
- (2) each, single interior outlets, 115 VAC, 1 phase, 60 Hz, 15 amp, NEMA L15 (1 per compartment)
- Clip-on generator set: 15 KW, 400/460 VAC, 3 Phase, 50-60 Hz
- Carrier reefer unit may be equipped with 30 amp CEE heavy-duty outlet with mechanical interlock switch to run only 1 reefer at a time
- Carrier reefer unit may be equipped with 60 amp CEE heavy-duty outlet, to run 2 reefers at a time. Also upgrade SO cable and 460 VAC plug to 60 amp rated
- De-humidity controls on the Carrier reefer unit
- Shelving (an upgrade from shelving) flat packed in cardboard box to be fully assembled and installed, strapped to the interior walls of the container



2 Light Switches on for each Compartment

ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD FOR NINE (9) HIGH STACKING

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
Ft in	19' 10 1/2"	17' 10 3/4"	8' 6"	7' 5 3/8"	8' 0"	7' 5 3/8"	7' 4 1/2"	7' 4"
Metric	6,058	5,455	2,591	2,250	2,438	2,270	2,248	2,235
	TARE WEIGHT		PAYLOAD		GROSS WEIGHT		CUBIC CAPACITY	
Lbs	6,060		45,780		52,910		985 Cu. Ft.	
Kgs	2,750		20,780		24,000		27.9 Cu. M.	

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

SB541-6-UN
 20' X 8' 6" Refrigerated ISO Cargo Container

030216-R01

ISO 9001



CERTIFIED QUALITY MANAGEMENT SYSTEM