



## 20' Insulated, Temperature Controlled Shelter (Type 6)

**SB6408**  
20' Insulated, Temperature Controlled Shelter (Type 6)



### PRODUCT FEATURES

#### STANDARD FEATURES

- Corrugated steel sides and roof
- 14 gauge insulated steel cargo doors one end
- Insulated, lockable man door other end
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs per 44 square inches
- Two-way laden fork lift pockets
- Recessed 2-ton Bard HVAC unit
- Insulated walls and ceiling
- Electrical system and fluorescent lighting



021007-R00BW

#### ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
<b>Ft in</b>	19' 10 1/2"	19'	8' 6"	7' 7 57/64"	8' 0"	7' 4"	7' 5 41/64"	7' 8 1/2"
<b>Metric</b>	6,058	5,791	2,591	2,334	2,438	2,235	2,277	2,350

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY
<b>Lbs</b>	9,100	43,810	52,910	1,167 Cu. Ft.
<b>Kgs</b>	4,128	19,872	24,000	33 Cu.M.

ISO 9001



CERTIFIED QUALITY MANAGEMENT SYSTEM

CONTRACT # GS-07F-253AA  
**GSA Advantage!**

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS