



**One Full Side Opening  
20' X 8' 6" Dry Freight ISO Cargo Container**

**SB891-6**  
One Full Side Opening  
20' X 8' 6" Dry Freight ISO Cargo Container



**STANDARD FEATURES**

- Corrugated steel ends, side, and bifold swing door on the side
- (2) sets of forklift pockets, laden and unladen
- 1 1/8" thick marine plywood floors, forklift tested to 16,000 lbs per 44 square inches
- Wall tie down steel lashing rings, 6,000 lbs. cap. each
- Corner post tie downs
- Floor recessed tie downs
- Vents, (2) each

**OPTIONAL FEATURES**

- E-track bracket system
- Heavy-duty adjustable shelving brackets (8) sets
- Decking and shoring beams

**ALL NEW CONTAINERS ARE MANUFACTURED TO THE LATEST ISO STANDARD**

	LENGTH		HEIGHT		WIDTH		DOOR OPENING	
	Exterior	Interior	Exterior	Interior	Exterior	Interior	Height	Width
<b>Ft in</b>	19' 10 1/2"	19' 6 11/32"	8' 6"	7' 5 11/64"	8' 0"	7' 6 43/64"	7' 0 17/32"	19' 5 25/32"
<b>Metric</b>	6,058	5,952	2,591	2,265	2,438	2,303	2,147	5,958

	TARE WEIGHT	PAYLOAD	GROSS WEIGHT	CUBIC CAPACITY
<b>Lbs</b>	6,530	46,380	52,910	1,094 cu. ft.
<b>Kgs</b>	2,960	21,040	24,000	31.0 cu. m.

ALL DIMENSIONS AND WEIGHTS ARE NOMINAL AND SUBJECT TO MINOR VARIATIONS THAT MAY OCCUR DURING THE MANUFACTURING PROCESS

022817-R01SS

ISO 9001



CERTIFIED QUALITY  
MANAGEMENT SYSTEM